



DATA SHEET

6.8MM ACOUSTIC LAMINATED

Comprising of two or more panes of glass which are bonded together using a specially designed high performance clear PVB interlayer. Various performances can be achieved by combing different types of glass thickness and number of interlayers.


TECHNICAL INFORMATION

Resistance to Fire	NPD
Reaction to Fire	NPD
External Fire Performance	NPD
Bullet Resistance	NPD
Explosion Resistance	NPD
Category of Resistance (EN 356)	P2A
Pendulum Body Impact Resistance	1(B)1
Resistance Against Sudden Temperature Changes and Temperature Differentials	40K
Wind, Snow, Permanent and Imposed Load Resistance	6 mm
Direct Airborne Sound Insulation	35 dB
THERMAL PROPERTIES	
Thermal Transmittance (U-value)	5.7 W/(m ² ,K)
RADIATION PROPERTIES	
Light Transmittance	0.89
Light Reflection	0.08
Solar Energy Transmission	0.77
Solar Energy Reflection	0.07

NPD = NO PERFORMANCE DETERMINED

KEY FEATURES

- Break safe characteristics
- Resists attack
- UV protection
- Improved acoustic performance
- Manufactured in accordance with EN 14449
- Minimised UV-transmission
- Sound control

 If you need help with any technical specifications, please email: technical@fireglassuk.com
We will be happy to help.

NATIONWIDE BRANCHES

MIDLANDS 0121 667 9089	NORTH 0161 532 8371	EAST 0121 667 9089	SOUTH 01206 805 922	SCOTLAND 0131 526 4141	INSTALLATION 0121 667 9089
----------------------------------	-------------------------------	------------------------------	-------------------------------	----------------------------------	--------------------------------------

