

TEL 0121 667 9089 EMAIL INFO@FIREGLASSUK.COM

WWW.FIREGLASSUK.COM



TECHNICAL FIRE SAFETY GROUP

MIDLANDS

NORTH

SOUTH

EAST

WEST

SCOTLAND



DATA SHEET

6MM FIRESAFE

6mm FireSafe is a high quality clear, toughened float glass which is fully recyclable. Ideal for a variety of applications in the exterior and interior of buildings.

TECHNICAL INFORMATION

Resistance to Fire	E30
Reaction to Fire	A1
External Fire Performance	NPD
Bullet Resistance	NPD
Explosion Resistance	NPD
Burglar Resistance	NPD
Pendulum Body Impact Resistance	1(C)1
Resistance Against Sudden Temperature Changes and Temperature Differentials	40K
Wind, Snow, Permanent and Imposed Load Resistance	6MM
Direct Airbourne Sound Insulation	31(-2;-3)dB
Thermal Properties	5.7W/(m2,K)
Radiation Properties	
Light Transmittance/ Reflectance	0.9/0.08
Solar Energy Transmission/ Reflectance	0.84/0.08
g Value	0.82
Durability	Pass
Normal Emissivity	0.89/0.89

KEY FEATURES

Highest quality float glass

Very high light transmission

Easily processed and fabricated

Manufactured in accordance with EN 572-2

Fully recyclable.

SUITABLE APPLICATION

Timber screens

Timber doors

Steel screens

STORAGE AND HANDLING

Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

If you need help with any technical specifications, please email: technical@fireglassuk.com We will be happy to help.

CERTIFIRE REF: 5319



PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

ACCREDITATION & CERTIFICATION -

















