



TECHNICAL FIRE SAFETY GROUP

SPECIALISTS IN FIRE RATED GLASS AND GLAZING TEL 0121 667 9089 EMAIL INFO@FIREGLASSUK.COM

WWW.FIREGLASSUK.COM

MIDLANDS

NORTH SOUT

SOUTH EAST

WEST SCOTLAND

INSTALLATION



DATA SHEET 8MM FIRESAFE

8mm FireSafe is a high quality clear, toughened float glass which is fully recyclable. Ideal for a variety of applications in the exterior and interior of buildings.

TECHNICAL INFORMATION

Resistance to Fire	E30
Reaction to Fire	A1
External Fire Performance	NPD
Bullet Resistance	NPD
Explosion Resistance	NPD
Burglar Resistance	NPD
Pendulum Body Impact Resistance	1(C)1
Resistance Against Sudden Temperature Changes and Temperature Differentials	40K
Wind, Snow, Permanent and Imposed Load Resistance	8MM
Direct Airbourne Sound Insulation	32(-2;-3)dB
Thermal Properties	5.6W/(m2,K)
Radiation Properties	
Light Transmittance/ Reflectance	89%
Solar Energy Transmission/ Reflectance	0.82/0.08
g Value	0.83
Durability	Pass
Normal Emissivity	0.89/0.89

KEY FEATURES



Highest quality float glass
Very high light transmission
Easily processed and fabricated

- Manufactured in accordance with EN 572-2
- Fully recyclable.

SUITABLE APPLICATION

Timber screens	5
----------------	---

- Timber doors
- Steel screens
- Steel doors

STORAGE AND HANDLING

Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

If you need help with any technical specifications, please email: technical@fireglassuk.com We will be happy to help.

CERTIFIRE REF: 5319

FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

Constructionline



ACCREDITATION & CERTIFICATION







certifire



Fire Glass UK Limited. Registered in England No. 6737753 at: 24-26 Hainge Road, Oldbury, West Midlands B69 2NH.