



DATA SHEET

15/19MM PYROGUARD

15mm/19mm Pyroguard offers protection against fire at reduced heat radiation.

TECHNICAL INFORMATION

Grade	Internal	External
Fire Classification	EW60/30* EI30	EW60/30* EI30
Glazing Type	Single	Single
Thickness	15mm	19mm
Thickness Tolerance	±1 mm	±1 mm
Dimensional Tolerance	±2 mm	±2 mm
Weight	37.6 kg/m ²	
Light Transmission (%)	85	85
UV Protection	No	No
Safety Rating (EN 14449)	Class 1(B)1	Class 1(B)1
Sound Reduction	38 dB	38 dB

KEY FEATURES

30|30 **60|30**

- Fire resistant EW60/30 / EI30
- Up to 60 minutes Integrity/30 minutes Insulation
- Interior and exterior use dependant on glass type
- Glazing integrity criterion EN 1363
- Multi-laminated

SUITABLE APPLICATION

- Can be used in steel & timber applications

STORAGE AND HANDLING

Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

If you need help with any technical specifications, please email: technical@fireglassuk.com
 We will be happy to help.

CERTIFIRE REF: CF437



FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

