

## DATASHEET

# 6.4mm Clear Laminated



Laminated glass comprises of two or more panes of glass which are bonded together using clear PVB interlayers. Different performances can be achieved by combing different combinations of glass thickness and number of interlayers.

### Technical Data

Resistance to Fire	NPD
Reaction to Fire	NPD
External Fire Performance	NPD
Bullet Resistance	NPD
Explosion Resistance	NPD
Category of Resistance	NPD
Pendulum Body Impact Resistance	2(B)2
Resistance Against Sudden Temperature Changes and Temperature Differentials	40K
Wind, Snow, Permanent and Imposed Load Resistance	6mm
Direct Airbourne Sound Insulation	32 (-1;-3)dB

### THERMAL PROPERTIES

Thermal Transmittance (U-value)	5.7 W/(m <sup>2</sup> ,K)
---------------------------------	---------------------------

### RADIATION PROPERTIES

Light Transmittance	0.89
Light Reflection	0.08
Solar Energy Transmission	0.77
Solar Energy Reflection	0.07

NPD = No Performance Determined

### Key Features

- ✓ Break safe characteristics
- ✓ Resists attack
- ✓ UV protection
- ✓ Improved acoustic performance
- ✓ Can be cut to size
- ✓ Manufactured in accordance with EN 14449
- ✓ Minimised UV-transmission



For more information about our products, give us call us on **0121 521 2180** or visit **[www.fireglassuk.com](http://www.fireglassuk.com)**

### NATIONWIDE BRANCHES

#### UK

Birmingham  
0121 521 2180

#### NORTH

Manchester  
0161 728 8080

#### EAST

Derby  
01773 712 920

#### SOUTH

Colchester  
01206 222 090

#### SCOTLAND

Edinburgh  
0131 526 4141