



DATA SHEET

# C730 7.2MM PYROGUARD

Pyroguard EW30 Impact is perfect for indoor and outdoor use. It's large sheet size and double sided fire resistance can be cut to size making it a cost effective solution.

TECHNICAL INFORMATION

Fire Classification	EW30
Impact Classification (EN14449)	2(B)2
Light Transmission	87%
Sound reduction	33 dB
U Value	5.1 W/m <sup>2</sup> K
UV Stability	Yes
Nominal Thickness	7 mm
Thickness Tolerance	-0.6 / +0.8 mm
Weight	17 kg per m <sup>2</sup>
Temperature Range	-20 / +140 °C
Sheet Size	1580 x 2780 mm

30  
0

KEY FEATURES

- EW30 fire classification
- 2(B)2 impact classification
- Interior and exterior use
- Double sided fire resistance
- UV stability
- Steel & timber applications

SUITABLE APPLICATION

- Can be used in fire tested timber and steel systems.

STORAGE AND HANDLING

- Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

If you need help, please email: [technical@fireglassuk.com](mailto:technical@fireglassuk.com)

CERTIFIRE REF: CF257

FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

ACCREDITATION & CERTIFICATION

