

DATASHEET

15mm / 19mm FireSafe



FireSafe offers protection against fire and smoke at reduced heat radiation.

Technical Data

	FireSafe Internal	FireSafe External
Fire Classification	EI60/30*	EI30/30*
Glazing Type	Single	Single
Grade	Internal	External
Thickness	15 mm	19 mm
Thickness Tolerance	±1 mm	±1 mm
Dimensional Tolerance	±2 mm	±2 mm
Weight	37.6 kg/m ²	
Light Transmission (%)	85	85
UV Protection	No	Yes
Safety Rating (EN 14449)	Class I(B)I	Class I(B)I
Sound Reduction	38dB	38dB

* Depending on application and size.

Key Features

- ✓ Fire resistant EI60/30 / EI30/30*
- ✓ 60 (45) minutes Integrity/30 minutes Insulation
- ✓ Interior and exterior use dependant on glass type
- ✓ Steel & Timber applications
- ✓ Glazing integrity criterion EN 1363
- ✓ Multi-laminated



For more information about our products, give us call us on **0121 521 2180** or visit www.fireglassuk.com

NATIONWIDE BRANCHES

UK	NORTH	EAST	SOUTH	SCOTLAND
Birmingham 0121 521 2180	Manchester 0161 728 8080	Derby 01773 712 920	Colchester 01206 222 090	Edinburgh 0131 526 4141