

DATASHEET

19mm FireSafe



19mm FireSafe is a fire rated glass that can withstand physical attack without failure.

Technical Information

| | |
|-----------------------|-----------------------------|
| Fire Classification | EW30 |
| Impact Classification | EN 12150 Pt. I, BS6206 |
| Light Transmission | 85.5% |
| Sound reduction | 40 dB |
| U Value | 5.04 W/m ² K |
| UV Stability | Yes |
| Nominal Thickness | 19mm |
| Thickness Tolerance | -0.6 / +0.8 mm |
| Weight | 47.50 kg per m ² |
| Temperature Range | -20 / +140 °C |

Key Features

- ✓ EW30 fire classification
- ✓ Class A impact classification
- ✓ Interior and exterior use
- ✓ Double sided fire resistance
- ✓ UV stability
- ✓ Timber applications



For more information about our products, give us call us on **0121 521 2180** or visit **www.fireglassuk.com**

NATIONWIDE BRANCHES

| | | | | |
|--|---|---------------------------------------|---|---|
| UK BIRMINGHAM 0121 521 2180 | NORTH MANCHESTER 0161 728 8080 | EAST DERBY 01773 712 920 | SOUTH COLCHESTER 01206 222 090 | SCOTLAND EDINBURGH 0131 526 4141 |
|--|---|---------------------------------------|---|---|