



DATA SHEET

11MM FIRE SWISS COOL

Fire Swiss Foam offers protection against fire at reduced heat radiation.

TECHNICAL INFORMATION

Fire Classification	EI30/EI60
Glazing Type	Single
Grade	Internal
Thickness	11 mm
Thickness Tolerance	±1 mm
Dimensional Tolerance	±2 mm
Weight	25 kg/m ²
Light Transmission (%)	87
UV Protection	No
Safety Rating (EN 14449)	Class 2(B)2
Sound Reduction	37 dB

KEY FEATURES

30
0

60
0

- Fire Resistant EI30/EI60
Dependant on Application
- 30 minute Integrity/60 minute Integrity dependent on application
- Interior Only
- Low Radiation Glass
- Glazing to Integrity Criterion EN 1363

SUITABLE APPLICATION

- Can be used in steel & timber applications

STORAGE AND HANDLING

- Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

- If you need help with any technical specifications, please email: technical@fireglassuk.com
We will be happy to help.



FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

