

DATASHEET

23mm Fire Swiss Foam



A multi-laminated glass assembled with clear intumescent interlayers. These layers expand and turn into a rigid and opaque fire shield at around 120°C, meeting the integrity criterion of EN 1363.

Technical Data

Fire Swiss

Fire Classification	EI60
Glazing Type	Single
Grade	Internal
Thickness	23 mm
Thickness Tolerance	±1 mm
Dimensional Tolerance	±2 mm
Weight	57.6 kg/m ²
Light Transmission (%)	82
UV Protection	No
Safety Rating (EN 14449)	Class I(B)I
Sound Reduction	40 dB

Key Features

- ✓ Fire resistant EI 60
- ✓ 60 minutes Integrity/60 minutes Insulation
- ✓ Interior and exterior use dependant on glass type
- ✓ Steel, aluminium and timber applications
- ✓ Glazing integrity criterion EN 1363
- ✓ Multi-laminated



For more information about our products, give us call us on **0121 521 2180** or visit **www.fireglassuk.com**

NATIONWIDE BRANCHES

UK	NORTH	EAST	SOUTH	SCOTLAND
Birmingham 0121 521 2180	Manchester 0161 728 8080	Derby 01773 712 920	Colchester 01206 222 090	Edinburgh 0131 526 4141