



**DATA SHEET**

# 7MM FIRE SWISS COOL

Fire Swiss Foam offers protection against fire at reduced heat radiation.

**TECHNICAL INFORMATION**

Fire Classification	EW30
Glazing Type	Single
Grade	Internal
Thickness	7 mm
Thickness Tolerance	±1 mm
Dimensional Tolerance	±2 mm
Weight	22 kg/m <sup>2</sup>
Light Transmission (%)	89
UV Protection	No
Safety Rating (EN 14449)	Class 3(B)3
Sound Reduction	35 dB

**30**  
**0**

**KEY FEATURES**

- Fire Resistant E30
- 30 minutes Integrity
- Interior only
- Low radiation glass
- Glazing to Integrity Criterion EN 1363

**SUITABLE APPLICATION**

- Can be used in steel & timber applications

**STORAGE AND HANDLING**

Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

If you need help, please email: [technical@fireglassuk.com](mailto:technical@fireglassuk.com)



**FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.**

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: [TECHNICAL@FIREGLASSUK.COM](mailto:TECHNICAL@FIREGLASSUK.COM)

